

View Online at <https://aerobasegroup.com/nsn/5340-01-224-4047>

First Leg Length:

Between 1.000 inches and 1.060 inches

Second Leg Length:

Between 1.160 inches and 1.220 inches

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.195 inches and 0.202 inches

Second Leg Hole Diameter:

Between 0.195 inches and 0.202 inches

Second Leg Distance Between Hole Centers Along Length:

1.080 mils and 1.140 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.280 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Thickness:

Between 0.030 inches and 0.050 inches

Second Leg Thickness:

Between 0.030 inches and 0.050 inches

First Leg Width:

Between 0.470 inches and 0.530 inches

First Leg Corner Radius:

0.120 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.470 inches and 0.490 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.09 radians

Special Features:

Includes two ms20426ad3 rivets, one ms21075l3 platenut

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-250/13 cond o federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0