

View Online at <https://aerobasegroup.com/nsn/5340-01-224-8276>

Mounting Hole Type:

Plain

First Leg Length:

2.250 inches

Second Leg Length:

5.500 inches

Reinforcement Method (non-core):

Raised center center section

Second Leg Width:

2.270 inches

Second Leg End Width:

2.250 inches

First Leg Slot Length:

0.810 inches

First Leg Slot Width:

0.500 inches

Second Leg Distance Between Hole Centers Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.062 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

Second Leg Slot Length:

1.250 inches

Second Leg Slot Width:

0.500 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

2.275 inches

First Leg End Width:

2.250 inches

First Leg Distance Between Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Second leg slots extend to end of leg

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200, t6 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Gps12-001, fscm 24930 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0