

View Online at <https://aerobasegroup.com/nsn/5340-01-224-9166>

Mounting Hole Type:

Plain and threaded

First Leg Length:

Between 1.220 inches and 1.280 inches

Second Leg Length:

Between 3.060 inches and 3.120 inches

Second Leg Width:

0.750 inches

Second Leg Corner Radius:

Between 0.090 inches and 0.150 inches

First Leg Slot Length:

Between 0.430 inches and 0.450 inches

First Leg Slot Width:

Between 0.380 inches and 0.390 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.287 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.355 inches and 0.395 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.470 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

0.625 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

0.875 inches

First Leg Thickness:

Between 0.370 inches and 0.380 inches

Second Leg Thickness:

Between 0.230 inches and 0.260 inches

First Leg Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.355 inches and 0.395 inches

First Leg Distance From Edge To Hole Center Along Length:

0.340 inches

First Leg End Radius:

0.375 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Center hole in second leg threaded 0.112-40 unc-2b

Material:

Steel comp 304

Material Specification:

Qq-s-766, cond a, finish 1 federal specification single material response or aisi 304 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-c-83286 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-83286 spec.