

View Online at <https://aerobasegroup.com/nsn/5340-01-224-9166>

**Mounting Hole Type:**

Plain and threaded

**First Leg Length:**

Between 1.220 inches and 1.280 inches

**Second Leg Length:**

Between 3.060 inches and 3.120 inches

**Second Leg Width:**

0.750 inches

**Second Leg Corner Radius:**

Between 0.090 inches and 0.150 inches

**First Leg Slot Length:**

Between 0.430 inches and 0.450 inches

**First Leg Slot Width:**

Between 0.380 inches and 0.390 inches

**Second Leg Hole Diameter:**

Between 0.276 inches and 0.287 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.355 inches and 0.395 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.470 inches

**Second Leg Distance Between First And Second Hole Centers Along Length:**

0.625 inches

**Second Leg Distance Between Second And Third Hole Centers Along Length:**

0.875 inches

**First Leg Thickness:**

Between 0.370 inches and 0.380 inches

**Second Leg Thickness:**

Between 0.230 inches and 0.260 inches

**First Leg Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.355 inches and 0.395 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.340 inches

**First Leg End Radius:**

0.375 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Center hole in second leg threaded 0.112-40 unc-2b

**Material:**

Steel comp 304

**Material Specification:**

Qq-s-766, cond a, finish 1 federal specification single material response or aisi 304 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-c-83286 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-83286 spec.