NSN 5340-01-224-9167

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-224-9167

Mounting Hole Type:
Plain
First Leg Length:
1.410 inches
Second Leg Length:
3.2496 inches
Second Leg Width:
5.120 inches
Second Leg Corner Radius:
0.500 inches
First Leg Hole Diameter:
0.406 inches
Second Leg Hole Diameter:
0.250 inches
Second Leg Distance Between Hole Centers Along Width:
3.880 inches
Second Leg Distance Between Hole Centers Along Length:
0.820 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.620 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.910 inches
First Leg Thickness:
0.1196 inches
Second Leg Thickness:
0.1196 inches
Center Section Height:
1.9996 inches
Center Section Width:
5.120 inches
Center Section Thickness:
0.1196 inches
First Leg Width:
5.120 inches
First Leg Distance Between Hole Centers Along Width:
3.620 inches
First Leg Distance From Edge To Hole Center Along Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Length:
0.620 inches
First Leg Style:
Square

NSN 5340-01-224-9167

Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
Four holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Special Features:
1 hole 2.190 in. Diameter located on second leg
Material:
Steel comp 1009 or steel
Material Specification:
Astm a366 assn standard 1st material response or astm a569 assn standard 1st material response or astm a109 assn standard 2nd material
response
Surface Treatment:
Phosphate zinc or paint or zinc and chromate or cadmium and chromate
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0