

View Online at <https://aerobasegroup.com/nsn/5340-01-226-4546>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.750 inches and 0.780 inches

Second Leg Length:

Between 1.550 inches and 1.580 inches

Second Leg Width:

Between 1.480 inches and 1.520 inches

Second Leg Corner Radius:

0.250 inches

Second Leg Hole Diameter:

Between 0.220 inches and 0.230 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.500 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

Between 1.480 inches and 1.520 inches

First Leg Corner Radius:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024 and aluminum alloy 1230

Material Specification:

Qq-a-250/5, t81 federal specification all material responses

Surface Treatment:

Plastic epoxy

Surface Treatment Specification:

Mil-p-23377 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-p-23377 spec.