

View Online at <https://aerobasegroup.com/nsn/5340-01-227-3484>

Mounting Hole Type:

Plain

First Leg Length:

2.500 inches

Second Leg Length:

3.620 inches

Second Leg Width:

1.750 inches

Second Leg End Width:

1.250 inches

First Leg Slot Length:

0.490 inches

First Leg Slot Width:

0.370 inches

Second Leg Hole Diameter:

Between 0.630 inches and 0.645 inches

Second Leg Distance Between Hole Centers Along Width:

0.562 inches

Second Leg Distance Between Hole Centers Along Length:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.563 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.625 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

1.750 inches

First Leg End Width:

1.250 inches

First Leg Distance Between Hole Centers Along Length:

0.500 inches

First Leg Style:

Chamfered ends

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

2 holes 0.136 in. Min and 0.151 in. Maximum diameter located on 2nd leg

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6, h321 or h323 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response

Surface Treatment:

Enamel semigloss

Surface Treatment Specification:

Tt-e-529, cl a federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0