

View Online at <https://aerobasegroup.com/nsn/5340-01-227-4884>

Mounting Hole Type:

Plain

First Leg Length:

5.250 inches

Second Leg Length:

6.750 inches

First Leg Hole Diameter:

0.203 mils and 0.219 centimeters

Second Leg Hole Diameter:

0.531 mils and 0.591 centimeters

Second Leg Distance Between Hole Centers Along Width:

3.465 inches

Second Leg Distance Between Hole Centers Along Length:

0.849 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.430 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

Center Section Height:

1.690 inches

Center Section Thickness:

0.190 inches

First Leg Distance Between Hole Centers Along Width:

6.000 inches

First Leg Distance Between Hole Centers Along Length:

3.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.560 inches

First Leg Hole Arrangement Style:

Four holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6, h321 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.