NSN 5340-01-227-4884

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-227-4884 **Mounting Hole Type:** Plain First Leg Length: 5.250 inches Second Leg Length: 6.750 inches First Leg Hole Diameter: 0.203 mils and 0.219 centimeters Second Leg Hole Diameter: 0.531 mils and 0.591 centimeters Second Leg Distance Between Hole Centers Along Width: 3.465 inches Second Leg Distance Between Hole Centers Along Length: 0.849 inches Second Leg Distance From Edge To Hole Center Along Width: 0.430 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.750 inches First Leg Thickness: 0.190 inches Second Leg Thickness: 0.190 inches **Center Section Height:** 1.690 inches **Center Section Thickness:** 0.190 inches First Leg Distance Between Hole Centers Along Width: 6.000 inches First Leg Distance Between Hole Centers Along Length: 3.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.560 inches First Leg Hole Arrangement Style: Four holes **Second Leg Hole Arrangement Style:** Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle:

90.0 degrees

NSN 5340-01-227-4884

Double Angle Bracket - Page 2 of 2

Mil-c-5541 spec.



Second Leg Angle:
90.0 degrees
Material:
Aluminum alloy 5083 or aluminum alloy 5086
Material Specification:
Qq-a-250/6, h321 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A042a0
Mil-std (military Standard):