

View Online at <https://aerobasegroup.com/nsn/5340-01-228-0653>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.532 inches

**Second Leg Length:**

0.532 inches

**Second Leg Width:**

1.316 inches

**First Leg Slot Length:**

0.250 inches

**First Leg Slot Width:**

0.145 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.660 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.650 inches

**Second Leg Slot Length:**

0.310 inches

**Second Leg Slot Width:**

0.125 inches

**First Leg Thickness:**

0.032 inches

**Second Leg Thickness:**

0.032 inches

**Center Section Height:**

0.124 inches

**Center Section Width:**

0.060 inches

**Center Section Thickness:**

0.032 inches

**First Leg Width:**

1.090 inches

**First Leg Distance Between Hole Centers Along Length:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.190 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl 3 military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.