## NSN 5340-01-228-1709

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-228-1709 First Leg Length: 1.123 inches Second Leg Length: 1.938 inches **End Application:** Truck dump m51a2 Second Leg Width: 3.250 inches First Leg Hole Diameter: 0.470 inches Second Leg Hole Diameter: 0.340 inches Second Leg Distance Between Hole Centers Along Width: 2.380 inches Second Leg Distance From Edge To Hole Center Along Width: 0.435 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.188 inches **Second Leg Thickness:** 0.188 inches **Center Section Height:** 5.380 inches **Center Section Width:** 3.250 inches **Center Section Thickness:** 0.188 inches First Leg Width: 3.250 inches First Leg Distance Between Hole Centers Along Width: 2.000 inches First Leg Distance From Edge To Hole Center Along Width: 0.625 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style:

Two holes

Second Leg Style:
Square

## NSN 5340-01-228-1709

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
Second Leg Angle:
73.0 degrees
First Leg Offset Angle:
90.0 degrees
Second Leg Offset Angle:
73.0 degrees
Material:
Steel comp 1010
Material Specification:
Qq-s-631 military specification single material response
Surface Treatment:
Primer and enamel
Surface Treatment Specification:
Tt-p-636 military specification 1st treatment response and tt-e-529 military specification 2nd treatment response
Style Designator:
Offset double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
snec