# NSN 5340-01-228-1709

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-228-1709

First Leg Length:
1.123 inches
Second Leg Length:
1.938 inches
End Application:
Truck dump m51a2
Second Leg Width:
3.250 inches
First Leg Hole Diameter:
0.470 inches
Second Leg Hole Diameter:
0.340 inches
Second Leg Distance Between Hole Centers Along Width:
2.380 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.435 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Thickness:
0.188 inches
Second Leg Thickness:
0.188 inches
Center Section Height:
5.380 inches
Center Section Width:
3.250 inches
Center Section Thickness:
0.188 inches
First Leg Width:
3.250 inches
First Leg Distance Between Hole Centers Along Width:
2.000 inches
First Leg Distance From Edge To Hole Center Along Width:
0.625 inches
First Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square

# NSN 5340-01-228-1709

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:

Two holes

## Second Leg Relationship To First Leg:

Not identical

## Second Leg Angle:

73.0 degrees

## First Leg Offset Angle:

90.0 degrees

## Second Leg Offset Angle:

73.0 degrees

Material:

Steel comp 1010

#### **Material Specification:**

Qq-s-631 military specification single material response

### Surface Treatment:

Primer and enamel

### Surface Treatment Specification:

Tt-p-636 military specification 1st treatment response and tt-e-529 military specification 2nd treatment response

### Style Designator:

Offset double angle

Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

#### Fiig:

A042a0

#### Mil-std (military Standard):

spec.