Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-228-3327

	bunting Hole Type:
	puntersunk and plain
	rst Leg Length:
	500 inches
Se	cond Leg Length:
0.5	500 inches
Se	cond Leg Width:
6.2	250 inches
Fir	rst Leg Hole Diameter:
Be	tween 0.188 inches and 0.191 inches
Se	cond Leg Hole Diameter:
0.0	098 inches
Se	cond Leg Distance From Edge To Hole Center Along Width:
0.5	500 inches
Se	cond Leg Distance From Edge To Hole Center Along Length:
0.2	220 inches
Fir	st Leg Thickness:
0.0	062 inches
Se	cond Leg Thickness:
0.0	062 inches
Fir	st Leg Width:
6.2	250 inches
Fir	st Leg Distance Between First And Second Hole Centers Along Width:
2.6	625 inches
Fir	st Leg Distance Between Second And Third Hole Centers Along Width:
2.6	625 inches
Fir	st Leg Distance From Edge To Hole Center Along Width:
0.5	500 inches
Fir	st Leg Distance From Edge To Hole Center Along Length:
0.1	190 inches
Fir	rst Leg Style:
Sq	uare
Fir	st Leg Hole Arrangement Style:
Th	ree holes
Se	cond Leg Style:
Sq	uare
Fe	atures Provided:
Nu	ıt
Se	cond Leg Relationship To First Leg:
No	t identical
Fir	rst Leg Angle:
	.0 degrees

NSN 5340-01-228-3327

Angle Bracket - Page 2 of 2



Special Features:

Second leg, six mtg holes spaced 1.050 in. Apart w/ 100 degrees csk by 0.180 in. Dia

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9, t5 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0