NSN 5340-01-229-2057



| NSN 5340-01-229-2057 ACT |
|---|
| Double Angle Bracket - Page 1 of 2 |
| View Online at https://aerobasegroup.com/nsn/5340-01-229-2057 |
| Mounting Hole Type: |
| Plain |
| First Leg Length: |
| 2.130 inches |
| Second Leg Length: |
| 2.995 inches |
| Second Leg Width: |
| 10.250 inches |
| First Leg Thickness: |
| 0.125 inches |
| Second Leg Thickness: |
| 0.125 inches |
| Center Section Height: |
| 1.185 inches |
| Center Section Width: |
| 10.250 inches |
| Center Section Thickness: |
| 0.125 inches |
| First Leg Width: |
| 10.250 inches |
| First Leg Distance Between Hole Centers Along Width: |
| 2.500 inches |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 90.0 degrees |
| Second Leg Angle: |
| 90.0 degrees |
| Special Features: |
| Gusset has slot cut edge 0.656 in. Min and 0.675 in. Maximum w by 1.083 in. Lg |
| Material: |
| Aluminum alloy 5083 or aluminum alloy 5086 |
| Material Specification: |
| Qq-a-250/6, h321 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response |
| Surface Treatment: |
| Chromate |
| Surface Treatment Specification: |
| Nil - FEAA - I A- williams and signal to start and a second |

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

NSN 5340-01-229-2057

Double Angle Bracket - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.

