

View Online at <https://aerobasegroup.com/nsn/5340-01-229-3560>

Mounting Hole Type:

Plain

First Leg Length:

2.500 inches

Second Leg Length:

2.500 inches

Second Leg Width:

4.000 inches

Second Leg End Width:

2.000 inches

First Leg Hole Diameter:

Between 0.499 inches and 0.504 inches

Second Leg Distance Between Hole Centers Along Width:

2.560 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.720 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.910 inches

Second Leg Slot Length:

1.120 inches

Second Leg Slot Width:

Between 0.400 inches and 0.450 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.000 inches

First Leg End Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Nut attached to hole on first leg

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-200/4, h111 federal specification 1st material response or qq-a-200/5, h111 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.