

View Online at <https://aerobasegroup.com/nsn/5340-01-230-6127>

Mounting Hole Type:

Plain

First Leg Length:

1.000 inches

Second Leg Length:

2.000 inches

Second Leg Width:

1.500 inches

First Leg Hole Diameter:

Between 0.220 inches and 0.231 inches

Second Leg Hole Diameter:

Between 0.143 inches and 0.154 inches

Second Leg Distance Between Hole Centers Along Width:

0.906 inches

Second Leg Distance Between Hole Centers Along Length:

0.906 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.297 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.427 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

1.500 inches

First Leg Distance Between Hole Centers Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.370 inches

First Leg Distance From Edge To Hole Center Along Length:

0.440 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Hole centered in holes 2nd leg 0.984 in. Min and 0.994 in. Maximum dia

Material:

Aluminum alloy 5052 or aluminum alloy 6061

Material Specification:

Qq-a-250/8, h32 federal specification 1st material response or qq-a-250/11, t6 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.