

View Online at <https://aerobasegroup.com/nsn/5340-01-231-1356>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.500 inches

**Second Leg Length:**

3.500 inches

**Second Leg Width:**

0.880 inches

**Second Leg End Width:**

0.500 inches

**First Leg Hole Diameter:**

Between 0.438 inches and 0.453 inches

**Second Leg Hole Diameter:**

Between 0.190 inches and 0.201 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.438 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

0.190 inches

**Second Leg Thickness:**

0.190 inches

**First Leg Width:**

0.880 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.438 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.406 inches

**First Leg End Radius:**

0.560 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086

**Material Specification:**

Qq-a-250/6, h321 or h323 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.