

View Online at <https://aerobasegroup.com/nsn/5340-01-231-1356>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

3.500 inches

Second Leg Width:

0.880 inches

Second Leg End Width:

0.500 inches

First Leg Hole Diameter:

Between 0.438 inches and 0.453 inches

Second Leg Hole Diameter:

Between 0.190 inches and 0.201 inches

Second Leg Distance Between Hole Centers Along Length:

2.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.438 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

First Leg Width:

0.880 inches

First Leg Distance From Edge To Hole Center Along Width:

0.438 inches

First Leg Distance From Edge To Hole Center Along Length:

0.406 inches

First Leg End Radius:

0.560 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6, h321 or h323 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.