NSN 5340-01-231-9291

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-231-9291 **Mounting Hole Type:** Plain First Leg Length: 3.030 inches Second Leg Length: 2.810 inches **End Application:** 2320-01-047-8754 truck, wrecker, w/w Second Leg Width: 5.120 inches First Leg Hole Diameter: 0.406 inches Second Leg Hole Diameter: 0.250 inches Second Leg Distance Between Hole Centers Along Width: 3.875 inches Second Leg Distance Between Hole Centers Along Length: 0.812 inches Second Leg Distance From Edge To Hole Center Along Width: 0.623 inches Second Leg Distance From Edge To Hole Center Along Length: 0.910 inches First Leg Thickness: 0.120 inches **Second Leg Thickness:** 0.120 inches First Leg Width: 5.120 inches First Leg Corner Radius: 0.500 inches First Leg Distance Between Hole Centers Along Width: 3.625 inches First Leg Distance From Edge To Hole Center Along Width: 0.750 inches First Leg Distance From Edge To Hole Center Along Length: 0.620 inches First Leg Style: Corner radius First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

NSN 5340-01-231-9291 Angle Bracket - Page 2 of 2



| Second Leg Hole Arrangement Style: | |
|---|--|
| Four holes | |
| Second Leg Relationship To First Leg: | |
| Not identical | |
| First Leg Angle: | |
| 90.0 degrees | |
| Special Features: | |
| Long leg contains (1) hole 2.190 in. Diameter on cl located 1.490in. From right angle, on 5.12in.Cl is 2.560 in. | |
| Material: | |
| Steel | |
| Material Specification: | |
| Qq-s-698 federal specification single material response | |
| Surface Treatment: | |
| Paint and zinc | |
| Surface Treatment Specification: | |
| Tt-p-636 federal specification single treatment response and tt-p-664 federal specification single treatment response | |
| Style Designator: | |
| Angle | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| - | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A042a0 | |
| | |