NSN 5340-01-235-1232

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-235-1232

Mounting Hole Type
Mounting Hole Type: Plain
First Leg Length: 1.510 inches
Second Leg Length:
1.640 inches
Second Leg Width:
0.620 inches
First Leg Hole Diameter:
0.098 inches
Second Leg Hole Diameter:
0.098 inches
Second Leg Distance Between Hole Centers Along Length:
0.750 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.310 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.310 inches
First Leg Thickness:
0.050 inches
Second Leg Thickness:
0.050 inches
First Leg Width:
0.620 inches
First Leg Distance Between Hole Centers Along Length:
0.620 inches
First Leg Distance From Edge To Hole Center Along Width:
0.310 inches
First Leg Distance From Edge To Hole Center Along Length:
0.310 inches
First Leg End Radius:
0.430 inches
Second Leg End Radius:
0.430 inches
First Leg Style:
End radius
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
End radius
Second Leg Hole Arrangement Style:

Two holes

NSN 5340-01-235-1232 Angle Bracket - Page 2 of 2



First Leg Angle: 93.0 degrees Second Leg Offset Angle: 102.0 degrees Material: Aluminum alloy 7075 and aluminum alloy 7072 Material Specification: Qq-a-250/13 federal specification single material response Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle Shelf Life:
93.0 degrees Second Leg Offset Angle: 102.0 degrees Material: Aluminum alloy 7075 and aluminum alloy 7072 Material Specification: Qq-a-250/13 federal specification single material response Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Second Leg Offset Angle: 102.0 degrees Material: Aluminum alloy 7075 and aluminum alloy 7072 Material Specification: Qq-a-250/13 federal specification single material response Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Material: Aluminum alloy 7075 and aluminum alloy 7072 Material Specification: Qq-a-250/13 federal specification single material response Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Material: Aluminum alloy 7075 and aluminum alloy 7072 Material Specification: Qq-a-250/13 federal specification single material response Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Aluminum alloy 7075 and aluminum alloy 7072 Material Specification: Qq-a-250/13 federal specification single material response Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Material Specification: Qq-a-250/13 federal specification single material response Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Qq-a-250/13 federal specification single material response Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Surface Treatment: Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Chromate zinc Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Surface Treatment Specification: Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Mil-p-8585 military specification single treatment response Style Designator: Offset angle
Style Designator: Offset angle
Offset angle
·
Shelf Life:
Onch Elic.
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-p-8585 spec.