

View Online at <https://aerobasegroup.com/nsn/5340-01-236-1859>

Mounting Hole Type:

Plain

First Leg Length:

1.510 inches

Second Leg Length:

1.640 inches

Second Leg Width:

0.620 inches

First Leg Hole Diameter:

0.098 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Length:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

0.620 inches

First Leg Distance Between Hole Centers Along Length:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg End Radius:

0.430 inches

Second Leg End Radius:

0.430 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

93.0 degrees

Second Leg Offset Angle:

78.0 degrees

Material:

Aluminum alloy 7075 or aluminum alloy 7072

Material Specification:

Qq-a-250/13 federal specification single material response

Surface Treatment:

Chromate zinc

Surface Treatment Specification:

Mil-p-8585 military specification single treatment response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-8585 spec.