## NSN 5340-01-236-2631

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-236-2631 **Mounting Hole Type:** Plain First Leg Length: 1.030 inches Second Leg Length: 3.780 inches Second Leg Width: 5.810 inches First Leg Hole Diameter: Between 0.311 inches and 0.322 inches Second Leg Hole Diameter: Between 0.311 inches and 0.322 inches Second Leg Distance Between Hole Centers Along Width: 4.630 inches Second Leg Distance From Edge To Hole Center Along Width: 0.590 inches Second Leg Distance From Edge To Hole Center Along Length: 0.590 inches First Leg Thickness: 0.090 inches Second Leg Thickness: 0.090 inches **Center Section Height:** 3.590 inches **Center Section Width:** 5.810 inches **Center Section Thickness:** 0.090 inches First Leg Width: 5.810 inches First Leg Distance From Edge To Hole Center Along Width: 0.590 inches Second Leg Style: Square Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 45.0 degrees

Second Leg Angle: 90.0 degrees

## NSN 5340-01-236-2631

Double Angle Bracket - Page 2 of 2

**Fiig:** A042a0



| First Leg Cutout Width:  |
|--|
| 1.190 inches   |
| Special Features:  |
| First leg furnished w/ a tab 1.100 in. Lg; 1.100 in. W, c/o hole   |
| Material:  |
| Aluminum alloy 2024 or aluminum alloy 6061   |
| Material Specification:  |
| Qq-a-250/4, t4 federal specification 1st material response or qq-a-250/11, t6 federal specification 2nd material response        |
| Surface Treatment:   |
| Paint  |
| Surface Treatment Specification:   |
| Tt-e-529, cl a federal specification single treatment response or tt-e-529, cl b federal specification single treatment response |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |