

View Online at <https://aerobasegroup.com/nsn/5340-01-237-4215>

**Mounting Hole Type:**

Plain

**End Application:**

F-15

**Second Leg Width:**

1.000 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.129 inches and 0.134 inches

**Second Leg Hole Diameter:**

Between 0.220 inches and 0.230 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.050 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.050 inches

**Center Section Height:**

0.500 inches

**Center Section Width:**

1.000 inches

**Center Section Thickness:**

0.050 inches

**First Leg Width:**

1.000 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

Item attached with rivets; requires clip nut, lh position

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5 t81 federal specification single material response

**Surface Treatment:**

Primer and chromate

**Surface Treatment Specification:**

Mil-p-23377 military specification 1st treatment response and mil-c-5541 military specification 2nd treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-p-23377 spec.