

View Online at <https://aerobasegroup.com/nsn/5340-01-238-5925>

Mounting Hole Type:

Plain and threaded

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.250 inches and 0.258 inches

Second Leg Hole Diameter:

Between 0.097 inches and 0.102 inches

Second Leg Distance Between Hole Centers Along Width:

0.125 inches

Second Leg Distance Between Hole Centers Along Length:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.250 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Nut, nas696c08 riveted to interior surf of second leg over 0.169 in. Min.0.174 in. Maximum diameter hole

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0