## NSN 5340-01-239-3574

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-239-3574

M
Mounting Hole Type:
Plain
First Leg Length:
1.380 inches
Second Leg Length:
1.380 inches
Second Leg Width:
8.000 inches
First Leg Hole Diameter:
0.380 inches
Second Leg Hole Diameter:
0.380 inches
Second Leg Distance Between Hole Centers Along Width:
5.190 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.380 inches
First Leg Thickness:
0.1196 inches
Second Leg Thickness:
0.1196 inches
First Leg Width:
8.000 inches
First Leg Distance Between Hole Centers Along Width:
7.000 inches
First Leg Distance From Edge To Hole Center Along Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Length:
0.6704 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Cut out
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees

## **NSN 5340-01-239-3574** Angle Bracket - Page 2 of 2



Second Leg Cutout Length:
0.250 inches
Second Leg Cutout Width:
2.000 inches
Special Features:
Color olive drab
Material:
Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015
Material Specification:
Mil-s-698, temper 2 to 5 military specification all material responses or sae, temper 2 to 5 assn standard all material responses
Surface Treatment:
Enamel semigloss
Surface Treatment Specification:
Tt-e-529 federal specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-s-698 spec.