NSN 5340-01-239-6454



Double Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-239-6454 **Mounting Hole Type:** Plain Second Leg Width: 1.500 inches **Second Leg Corner Radius:** 0.250 inches First Leg Hole Diameter: Between 0.220 inches and 0.230 inches First Leg Thickness: 0.050 inches Second Leg Thickness: 0.050 inches **Center Section Height:** 0.500 inches **Center Section Width:** 1.500 inches **Center Section Thickness:** 0.050 inches First Leg Width: 1.500 inches First Leg Corner Radius: 0.250 inches First Leg Distance Between Hole Centers Along Width: 1.000 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.240 inches and 0.260 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Corner radius First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius **Second Leg Hole Arrangement Style:** No hole Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees

Second Leg Angle: 90.0 degrees

NSN 5340-01-239-6454

Double Angle Bracket - Page 2 of 2

Mil-p-23377 spec.



Special Features:
Includes p/n st3m523c3m clipnut w/o rivet holes right handed
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-250/5 t81 federal specification single material response
Surface Treatment:
Primer and chromate
Surface Treatment Specification:
Mil-p-23377 military specification 1st treatment response and mil-c-5541 military specification 2nd treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):