

View Online at <https://aerobasegroup.com/nsn/5340-01-240-8941>

**Mounting Hole Type:**

Plain

**First Leg Length:**

3.500 inches

**Second Leg Length:**

6.000 inches

**Second Leg Width:**

Between 21.970 inches and 22.030 inches

**First Leg Hole Diameter:**

Between 0.560 inches and 0.567 inches

**Second Leg Hole Diameter:**

Between 0.560 inches and 0.567 inches

**Second Leg Distance Between Hole Centers Along Width:**

16.875 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

5.625 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

5.625 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

2.560 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.560 inches

**First Leg Thickness:**

0.500 inches

**Second Leg Thickness:**

0.500 inches

**First Leg Width:**

Between 21.970 inches and 22.030 inches

**First Leg Distance Between Hole Centers Along Width:**

16.875 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

2.812 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

2.812 inches

**First Leg Distance From Edge To Hole Center Along Width:**

2.562 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.520 inches

**First Leg Style:**

Square

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First leg furnished w/ six holes; bracket painted gray no. lii

**Material:**

Steel

**Material Specification:**

Astm a36 assn standard single material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-150901, type 3 cl 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-e-150901 spec.