

View Online at <https://aerobasegroup.com/nsn/5340-01-240-8941>

Mounting Hole Type:

Plain

First Leg Length:

3.500 inches

Second Leg Length:

6.000 inches

Second Leg Width:

Between 21.970 inches and 22.030 inches

First Leg Hole Diameter:

Between 0.560 inches and 0.567 inches

Second Leg Hole Diameter:

Between 0.560 inches and 0.567 inches

Second Leg Distance Between Hole Centers Along Width:

16.875 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

5.625 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

5.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.560 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.560 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

Between 21.970 inches and 22.030 inches

First Leg Distance Between Hole Centers Along Width:

16.875 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.812 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

2.812 inches

First Leg Distance From Edge To Hole Center Along Width:

2.562 inches

First Leg Distance From Edge To Hole Center Along Length:

1.520 inches

First Leg Style:

Square

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg furnished w/ six holes; bracket painted gray no. lii

Material:

Steel

Material Specification:

Astm a36 assn standard single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-150901, type 3 cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-e-150901 spec.