Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-01-242-4371



PlainFirst Leg Length:0.812 inchesSecond Leg Length:1.000 inchesReinforcement Method (non-core):Turned edge second legSecond Leg Width:2.688 inchesFirst Leg Hole Diameter:Between 0.190 inches and 0.194 inchesSecond Leg Hole Diameter:Between 0.218 inches and 0.229 inchesSecond Leg Distance Between Hole Centers Along Length:2.000 inches
0.812 inches Second Leg Length: 1.000 inches Reinforcement Method (non-core): Turned edge second leg Second Leg Width: 2.688 inches First Leg Hole Diameter: Between 0.190 inches and 0.194 inches Second Leg Hole Diameter: Between 0.218 inches and 0.229 inches Second Leg Distance Between Hole Centers Along Length: 2.000 inches
Second Leg Length: 1.000 inches Reinforcement Method (non-core): Turned edge second leg Second Leg Width: 2.688 inches First Leg Hole Diameter: Between 0.190 inches and 0.194 inches Second Leg Hole Diameter: Between 0.218 inches and 0.229 inches Second Leg Distance Between Hole Centers Along Length: 2.000 inches
<ul> <li>1.000 inches</li> <li>Reinforcement Method (non-core):</li> <li>Turned edge second leg</li> <li>Second Leg Width:</li> <li>2.688 inches</li> <li>First Leg Hole Diameter:</li> <li>Between 0.190 inches and 0.194 inches</li> <li>Second Leg Hole Diameter:</li> <li>Between 0.218 inches and 0.229 inches</li> <li>Second Leg Distance Between Hole Centers Along Length:</li> <li>2.000 inches</li> </ul>
Reinforcement Method (non-core):Turned edge second legSecond Leg Width:2.688 inchesFirst Leg Hole Diameter:Between 0.190 inches and 0.194 inchesSecond Leg Hole Diameter:Between 0.218 inches and 0.229 inchesSecond Leg Distance Between Hole Centers Along Length:2.000 inches
Turned edge second leg Second Leg Width: 2.688 inches First Leg Hole Diameter: Between 0.190 inches and 0.194 inches Second Leg Hole Diameter: Between 0.218 inches and 0.229 inches Second Leg Distance Between Hole Centers Along Length: 2.000 inches
Second Leg Width: 2.688 inches First Leg Hole Diameter: Between 0.190 inches and 0.194 inches Second Leg Hole Diameter: Between 0.218 inches and 0.229 inches Second Leg Distance Between Hole Centers Along Length: 2.000 inches
<ul> <li>2.688 inches</li> <li>First Leg Hole Diameter:</li> <li>Between 0.190 inches and 0.194 inches</li> <li>Second Leg Hole Diameter:</li> <li>Between 0.218 inches and 0.229 inches</li> <li>Second Leg Distance Between Hole Centers Along Length:</li> <li>2.000 inches</li> </ul>
First Leg Hole Diameter: Between 0.190 inches and 0.194 inches Second Leg Hole Diameter: Between 0.218 inches and 0.229 inches Second Leg Distance Between Hole Centers Along Length: 2.000 inches
Between 0.190 inches and 0.194 inches Second Leg Hole Diameter: Between 0.218 inches and 0.229 inches Second Leg Distance Between Hole Centers Along Length: 2.000 inches
Second Leg Hole Diameter: Between 0.218 inches and 0.229 inches Second Leg Distance Between Hole Centers Along Length: 2.000 inches
Between 0.218 inches and 0.229 inches Second Leg Distance Between Hole Centers Along Length: 2.000 inches
Second Leg Distance Between Hole Centers Along Length: 2.000 inches
2.000 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.625 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.375 inches
First Leg Width:
4.312 inches
First Leg Distance Between Hole Centers Along Length:
0.934 inches
First Leg Distance From Edge To Hole Center Along Width:
0.438 inches
First Leg Distance From Edge To Hole Center Along Length:
2.937 inches
First Leg Hole Arrangement Style:
Two holes
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Material:
Aluminum alloy 2024
Style Designator:
Angle
Shelf Life:
N/a

## NSN 5340-01-242-4371

Angle Bracket - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A042a0

