

View Online at <https://aerobasegroup.com/nsn/5340-01-243-9718>

**Thread Class:**

3b left internal (includes through thread)

**Thread Direction:**

Right-hand right external

**Thread Length:**

0.5000 inches right external

**Shoulder Diameter:**

Between 0.3040 inches and 0.3160 inches

**Shoulder Length:**

0.1250 inches

**Second Shoulder Diameter:**

0.3470 inches

**Second Shoulder Length:**

0.0800 inches

**Length:**

1.5000 inches

**Cross-sectional Shape:**

Hexagon

**Width Across Flats:**

Between 0.3040 inches and 0.3160 inches

**Thready Qty Per Inch (tpi):**

32 right external

**Thread Size:**

0.1900 inches left internal (includes through thread)

**Material:**

Steel comp 4130 standoff or steel comp 4140 standoff or steel comp 8740 standoff or steel comp 8630 standoff

**Material Specification:**

Mil-s-6758 military specification single material response standoff or mil-s-5626 military specification single material response standoff or mil-s-6040 military specification single material response standoff or mil-s-6050 military specification single material response standoff

**Surface Treatment:**

Cadmium standoff and chromate standoff

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response standoff

**Style Designator:**

Two shoulders left internal and right external threads

**Thread Series Designator:**

Unjf right external

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A08900

**Mil-std (military Standard):**

Mil-s-6758 spec.