

View Online at <https://aerobasegroup.com/nsn/5340-01-243-9718>

Thread Class:

3b left internal (includes through thread)

Thread Direction:

Right-hand right external

Thread Length:

0.5000 inches right external

Shoulder Diameter:

Between 0.3040 inches and 0.3160 inches

Shoulder Length:

0.1250 inches

Second Shoulder Diameter:

0.3470 inches

Second Shoulder Length:

0.0800 inches

Length:

1.5000 inches

Cross-sectional Shape:

Hexagon

Width Across Flats:

Between 0.3040 inches and 0.3160 inches

Thready Qty Per Inch (tpi):

32 right external

Thread Size:

0.1900 inches left internal (includes through thread)

Material:

Steel comp 4130 standoff or steel comp 4140 standoff or steel comp 8740 standoff or steel comp 8630 standoff

Material Specification:

Mil-s-6758 military specification single material response standoff or mil-s-5626 military specification single material response standoff or mil-s-6040 military specification single material response standoff or mil-s-6050 military specification single material response standoff

Surface Treatment:

Cadmium standoff and chromate standoff

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response standoff

Style Designator:

Two shoulders left internal and right external threads

Thread Series Designator:

Unjf right external

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A08900

Mil-std (military Standard):

Mil-s-6758 spec.