

View Online at <https://aerobasegroup.com/nsn/5340-01-244-1136>

Mounting Hole Type:

Counterbored

First Leg Length:

1.000 inches

Second Leg Length:

2.380 inches

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

Between 0.220 inches and 0.225 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.200 inches

Second Leg Slot Length:

0.658 inches

Second Leg Slot Width:

Between 0.453 inches and 0.463 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

6.980 inches

First Leg Distance Between Hole Centers Along Width:

4.092 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.280 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.280 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Six captive screws incl; color gray; first leg angled 15 degrees from weld to end

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Plastic epoxy

Surface Treatment Specification:

Mil-c-22750 type 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.