

View Online at <https://aerobasegroup.com/nsn/5340-01-244-2353>

**Mounting Hole Type:**

Counterbored

**First Leg Length:**

1.000 inches

**Second Leg Length:**

1.200 inches

**Second Leg Width:**

3.000 inches

**First Leg Hole Diameter:**

Between 0.220 inches and 0.225 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.825 inches

**Second Leg Slot Length:**

0.658 inches

**Second Leg Slot Width:**

Between 0.453 inches and 0.463 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

6.980 inches

**First Leg Distance Between Hole Centers Along Width:**

4.092 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.280 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

1.280 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.300 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Six captive screws incl; color gray; first leg angled 15 degrees from weld to end

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Plastic epoxy

**Surface Treatment Specification:**

Mil-c-22750 type 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-22750 spec.