NSN 5340-01-244-7116

Butt Hinge - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-244-7116

Overall Length:
37.320 inches
Material Thickness:
Between 0.044 inches and 0.056 inches
Mounting Hole Diameter:
0.128 inches
Mounting Hole Quantity:
18
Pin Diameter:
Between 0.093 inches and 0.098 inches
Mounting Method:
Unthreaded holes
Performance Type:
Not rated
Reversible Feature:
Not included
Pin Removability:
Removable
Rising Pin:
Not included
Knuckle Quantity:
Knuckle Quantity: 39
39
39 Pin Center To Body Edge Distance:
39 Pin Center To Body Edge Distance: 0.625 inches
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type:
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location:
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location:
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location: Anodized, mil-a-8625, type 1, class 1 and chromate
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location: Anodized, mil-a-8625, type 1, class 1 and chromate Style Designator:
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location: Anodized, mil-a-8625, type 1, class 1 and chromate Style Designator: Butt
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location: Anodized, mil-a-8625, type 1, class 1 and chromate Style Designator: Butt Shelf Life:
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location: Anodized, mil-a-8625, type 1, class 1 and chromate Style Designator: Butt Shelf Life: N/a
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location: Anodized, mil-a-8625, type 1, class 1 and chromate Style Designator: Butt Shelf Life: N/a
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location: Anodized, mil-a-8625, type 1, class 1 and chromate Style Designator: Butt Shelf Life: N/a Unit Of Measure:
Pin Center To Body Edge Distance: 0.625 inches Knuckle Type: Friction Material And Location: Aluminum alloy, qq-a-200/3, alloy 2024, t3511 or aluminum alloy, qq-a-200/11, t73511 Surface Treatment And Location: Anodized, mil-a-8625, type 1, class 1 and chromate Style Designator: Butt Shelf Life: N/a Unit Of Measure: Demilitarization: