

View Online at <https://aerobasegroup.com/nsn/5340-01-245-3237>

Mounting Hole Type:

Plain

First Leg Length:

0.800 inches

Second Leg Length:

1.000 inches

Second Leg Width:

2.312 inches

First Leg Hole Diameter:

Between 0.133 inches and 0.139 inches

Second Leg Hole Diameter:

Between 0.154 inches and 0.156 inches

Second Leg Distance Between Hole Centers Along Width:

1.810 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.085 inches and 0.095 inches

Second Leg Thickness:

Between 0.085 inches and 0.095 inches

First Leg Width:

2.310 inches

First Leg Distance Between Hole Centers Along Width:

1.312 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

0.500 inches

First Leg Cutout Width:

Between 1.135 inches and 1.145 inches

Second Leg Cutout Length:

0.500 inches

Second Leg Cutout Width:

1.430 inches

Special Features:

First leg cut out radius 0.060 in., cut on a 10 degrees angle

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.