

View Online at <https://aerobasegroup.com/nsn/5340-01-247-7627>

Mounting Hole Type:

Plain

First Leg Length:

7.000 inches

Second Leg Length:

Between 6.990 inches and 7.010 inches

Second Leg Width:

3.500 inches

First Leg Slot Width:

Between 0.235 inches and 0.265 inches

Second Leg Hole Diameter:

0.302 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

Between 1.999 inches and 2.001 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

Between 1.999 inches and 2.001 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

Between 2.219 inches and 2.249 inches

First Leg Distance From Edge To Hole Center Along Length:

1.047 inches

First Leg Distance Between First And Second Hole Centers Along Length:

Between 2.235 inches and 2.265 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

3.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

3 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.06 radians

Special Features:

Has duplicate row of holes 2.000 in. C to c along width from 1st row of holes; opposite of p/n 0n008930-1 nsn 5340-01-243-5163 right hand

Material:

Steel comp 1009 and steel comp 1010 and steel comp 1011 and steel comp 1012 and steel comp 1013 and steel comp 1015 and steel comp 1016 and steel comp 1017 and steel comp 1018 and steel comp 1019 and steel comp 1020

Material Specification:

Qq-s-698 federal specification all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.