NSN 5340-01-249-4283

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-249-4283

| Mounting Hole Type: |
|--|
| Plain |
| First Leg Length: |
| 1.380 inches |
| Second Leg Length: |
| 2.380 inches |
| Second Leg Width: |
| 4.625 inches |
| Second Leg End Width: |
| 4.375 inches |
| First Leg Hole Diameter: |
| Between 0.312 inches and 0.344 inches |
| Second Leg Hole Diameter: |
| Between 0.484 inches and 0.516 inches |
| Second Leg Distance Between Hole Centers Along Width: |
| 3.625 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.500 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.620 inches |
| First Leg Thickness: |
| 0.125 inches |
| Second Leg Thickness: |
| 0.125 inches |
| First Leg Width: |
| 4.625 inches |
| First Leg End Width: |
| 4.375 inches |
| First Leg Distance Between Hole Centers Along Width: |
| 3.625 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| 0.500 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| 0.500 inches |
| First Leg Style: |
| Chamfered ends |
| First Leg Hole Arrangement Style: |
| Two holes |
| Second Leg Style: |
| Chamfered ends |
| Second Leg Hole Arrangement Style: |
| Two holes |
| |

NSN 5340-01-249-4283 Angle Bracket - Page 2 of 2



| Second Leg Relationship To First Leg: |
|--|
| dentical |
| First Leg Angle: |
| 90.0 degrees |
| Special Features: |
| Color forest green |
| Material: |
| Aluminum alloy 5083 or aluminum alloy 5086 |
| Material Specification: |
| Qq-a-250/6, h325 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response |
| Surface Treatment: |
| Enamel |
| Surface Treatment Specification: |
| Mil-e-52835 military specification single treatment response or mil-e-52798 military specification single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A042a0 |
| Mil-std (military Standard): |
| Mil-e-52835 spec. |