

View Online at <https://aerobasegroup.com/nsn/5340-01-249-4283>

Mounting Hole Type:

Plain

First Leg Length:

1.380 inches

Second Leg Length:

2.380 inches

Second Leg Width:

4.625 inches

Second Leg End Width:

4.375 inches

First Leg Hole Diameter:

Between 0.312 inches and 0.344 inches

Second Leg Hole Diameter:

Between 0.484 inches and 0.516 inches

Second Leg Distance Between Hole Centers Along Width:

3.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

4.625 inches

First Leg End Width:

4.375 inches

First Leg Distance Between Hole Centers Along Width:

3.625 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Special Features:

Color forest green

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6, h325 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-52835 military specification single treatment response or mil-e-52798 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-e-52835 spec.