

View Online at <https://aerobasegroup.com/nsn/5340-01-249-4284>

Mounting Hole Type:

Countersunk and threaded

First Leg Length:

1.560 inches

Second Leg Length:

1.620 inches

Second Leg Width:

1.880 inches

First Leg Hole Diameter:

0.406 inches

Second Leg Hole Diameter:

Between 0.124 inches and 0.129 inches

Second Leg Distance Between Upper Hole Centers Along Width:

1.500 inches

Second Leg Distance Between Hole Centers Along Length:

0.560 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.750 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.190 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

1.880 inches

First Leg End Width:

1.085 inches

First Leg Distance From Edge To Hole Center Along Width:

0.940 inches

First Leg Distance From Edge To Hole Center Along Length:

0.370 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Cincl two nuts ms14200-06-6; one 0.132 in. Min 0.138 in. Maximum diameter through hole in first leg spaced 0.531 in. From ctr of 0.406 in.

Diameter hole on a centerline offset 21.0 deg; marked e10, c1, e11, r4, e12, r5

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.