NSN 5340-01-249-7910

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-249-7910 First Leg Length: 1.000 inches Second Leg Length: 2.880 inches Second Leg Width: 2.500 inches First Leg Slot Length: 1.060 inches First Leg Slot Width: 0.410 inches Second Leg Hole Diameter: 0.295 inches Second Leg Distance Between Upper Hole Centers Along Width: 2.000 inches Second Leg Distance Between Hole Centers Along Length: 1.500 inches Second Leg Distance Between First And Second Hole Centers Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.190 inches **Second Leg Thickness:** 0.190 inches **Center Section Height:** 0.780 inches **Center Section Width:** 2.500 inches **Center Section Thickness:** 0.190 inches First Leg Width: 2.500 inches First Leg End Width: 0.620 inches First Leg Distance From Edge To Hole Center Along Width: 1.250 inches First Leg Distance From Edge To Hole Center Along Length: 0.630 inches

First Leg Style:

Square and tapered

NSN 5340-01-249-7910

Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
One slot
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
60.3 degrees
Second Leg Angle:
60.3 degrees
Material:
Steel comp 304 or steel comp 316
Material Specification:
Astm-a240 assn standard single material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
. -
Demilitarization:
No
Fiig:
A042a0