Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-01-249-8151



Mounting Hole Type:
Plain
First Leg Length:
2.000 inches
Second Leg Length:
8.600 inches
Second Leg Width:
8.000 inches
First Leg Hole Diameter:
0.219 mils and 0.226 centimeters
Second Leg Hole Diameter:
0.232 mils and 0.239 centimeters
Second Leg Distance Between Hole Centers Along Width:
5.732 inches
Second Leg Distance Between Hole Centers Along Length:
5.732 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
2.866 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
2.866 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.100 inches
Second Leg Distance From Edge To Hole Center Along Length:
2.500 inches
First Leg Thickness:
0.250 inches
Second Leg Thickness:
0.250 inches
First Leg Width:
8.000 inches
First Leg Distance Between Hole Centers Along Width:
6.000 inches
First Leg Distance Between First And Second Hole Centers Along Width:
2.000 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
2.000 inches
First Leg Distance From Edge To Hole Center Along Width:
1.000 inches
First Leg Distance From Edge To Hole Center Along Length:
0.350 inches
First Leg Style:
Square

# NSN 5340-01-249-8151

Angle Bracket - Page 2 of 2



#### First Leg Hole Arrangement Style:

Four holes

#### Second Leg Style:

Square

#### Second Leg Relationship To First Leg:

Not identical

#### First Leg Angle:

90.0 degrees

#### Material:

Aluminum alloy 6061

#### **Material Specification:**

Qq-a-250/11, t6 federal specification single material response

#### Surface Treatment:

Chromate

#### Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

#### Style Designator:

Angle

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

## Fiig:

A042a0

### Mil-std (military Standard):

Mil-c-5541 spec.