NSN 5340-01-249-8151

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-249-8151

3
Mounting Hole Type:
Plain
First Leg Length:
2.000 inches
Second Leg Length:
8.600 inches
Second Leg Width:
8.000 inches
First Leg Hole Diameter:
0.219 mils and 0.226 centimeters
Second Leg Hole Diameter:
0.232 mils and 0.239 centimeters
Second Leg Distance Between Hole Centers Along Width:
5.732 inches
Second Leg Distance Between Hole Centers Along Length:
5.732 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
2.866 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
2.866 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.100 inches
Second Leg Distance From Edge To Hole Center Along Length:
2.500 inches
First Leg Thickness:
0.250 inches
Second Leg Thickness:
0.250 inches
First Leg Width:
8.000 inches
First Leg Distance Between Hole Centers Along Width:
6.000 inches
First Leg Distance Between First And Second Hole Centers Along Width:
2.000 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
2.000 inches
First Leg Distance From Edge To Hole Center Along Width:
1.000 inches
First Leg Distance From Edge To Hole Center Along Length:
0.350 inches
First Leg Style:

Square

NSN 5340-01-249-8151 Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Four holes
Second Leg Style:
Square
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, t6 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.