

View Online at <https://aerobasegroup.com/nsn/5340-01-249-8151>

Mounting Hole Type:

Plain

First Leg Length:

2.000 inches

Second Leg Length:

8.600 inches

Second Leg Width:

8.000 inches

First Leg Hole Diameter:

0.219 mils and 0.226 centimeters

Second Leg Hole Diameter:

0.232 mils and 0.239 centimeters

Second Leg Distance Between Hole Centers Along Width:

5.732 inches

Second Leg Distance Between Hole Centers Along Length:

5.732 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

2.866 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

2.866 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.100 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

8.000 inches

First Leg Distance Between Hole Centers Along Width:

6.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.350 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.