

View Online at <https://aerobasegroup.com/nsn/5340-01-250-7998>

Mounting Hole Type:

Plain and threaded

Second Leg Length:

Between 1.430 inches and 1.470 inches

Second Leg Width:

1.100 inches

Second Leg End Width:

0.900 inches

First Leg Hole Diameter:

Between 0.167 inches and 0.175 inches

Second Leg Hole Diameter:

0.085 inches

Second Leg Distance Between Hole Centers Along Width:

0.812 inches

Second Leg Distance Between Hole Centers Along Length:

0.812 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.144 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.144 inches

First Leg Thickness:

0.080 inches

Second Leg Thickness:

0.080 inches

First Leg Distance From Edge To Hole Center Along Width:

0.190 inches

First Leg Distance From Edge To Hole Center Along Length:

0.190 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Chamfer Angle:

Between 40.0 degrees and 50.0 degrees

Special Features:

Cutout 2nd leg 0.956 dp, 0.620 in. W

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.