# NSN 5340-01-251-1997

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-251-1997

Mounting Hole Type:
Plain
First Leg Length:
Between 2.320 inches and 2.420 inches
Second Leg Length:
Between 2.320 inches and 2.420 inches
Second Leg Width:
3.450 mils and 3.550 centimeters
First Leg Hole Diameter:
0.625 inches
Second Leg Hole Diameter:
0.216 mils and 0.223 centimeters
Second Leg Distance Between Hole Centers Along Width:
2.000 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.380 inches
First Leg Thickness:
0.125 inches
Second Leg Thickness:
0.125 inches
Center Section Height:
2.330 inches
Center Section Thickness:
0.125 inches
First Leg Width:
Between 3.450 inches and 3.550 inches
First Leg Distance Between Hole Centers Along Width:
1.880 inches
First Leg Distance Between Hole Centers Along Length:
2.250 inches
First Leg Distance From Edge To Hole Center Along Width:
0.810 inches
First Leg Distance From Edge To Hole Center Along Length:
0.380 inches
Second Leg Style:
Extended flat
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical

## NSN 5340-01-251-1997

Double Angle Bracket - Page 2 of 2



First Leg Angle:

90.0 degrees

#### Second Leg Angle:

90.0 degrees

### **Special Features:**

Multiple holes in first leg; third hole in second leg 0.625 in. Dia

## Surface Treatment:

Chromate

## Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A042a0

#### Mil-std (military Standard):

Mil-c-5541 spec.