NSN 5340-01-251-1997

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-251-1997

Mounting Hole Type:

Plain

First Leg Length:

Between 2.320 inches and 2.420 inches

Second Leg Length:

Between 2.320 inches and 2.420 inches

Second Leg Width:

3.450 mils and 3.550 centimeters

First Leg Hole Diameter:

0.625 inches

Second Leg Hole Diameter:

0.216 mils and 0.223 centimeters

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

2.330 inches

Center Section Thickness:

0.125 inches

First Leg Width:

Between 3.450 inches and 3.550 inches

First Leg Distance Between Hole Centers Along Width:

1.880 inches

First Leg Distance Between Hole Centers Along Length:

2.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.810 inches

First Leg Distance From Edge To Hole Center Along Length:

0.380 inches

Second Leg Style:

Extended flat

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

NSN 5340-01-251-1997

Double Angle Bracket - Page 2 of 2



First Leg Angle:	
90.0 degrees	
Second Leg Angle:	
90.0 degrees	
Special Features:	
Multiple holes in first leg; third hole in second leg 0.625 in. Dia	
Surface Treatment:	
Chromate	
Surface Treatment Specification:	
Mil-c-5541, cl 1a military specification single treatment response	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A042a0	
Mil-std (military Standard):	
Mil-c-5541 spec.	