

View Online at <https://aerobasegroup.com/nsn/5340-01-251-6409>

**Mounting Hole Type:**

Threaded

**First Leg Length:**

0.750 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

4.000 inches

**First Leg Hole Diameter:**

0.149 inches

**Second Leg Hole Diameter:**

0.164 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.125 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

2.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

0.500 inches

**Second Leg Thickness:**

0.500 inches

**First Leg Width:**

4.000 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.813 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

1.562 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.313 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Second leg has additional hole 0.625 in. Min and 0.626 in. Maximum diameter 0.750 in. From end centered on w of leg; one hole 0.093 in. Diameter 2.500 in. From 5/8 diameter hole and 0.750 in. From bottom

**Material:**

Steel or steel comp 1008 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1017 or steel comp 1020

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0