

View Online at <https://aerobasegroup.com/nsn/5340-01-251-6409>

Mounting Hole Type:

Threaded

First Leg Length:

0.750 inches

Second Leg Length:

1.000 inches

Second Leg Width:

4.000 inches

First Leg Hole Diameter:

0.149 inches

Second Leg Hole Diameter:

0.164 inches

Second Leg Distance Between Hole Centers Along Width:

1.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

4.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.813 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.562 inches

First Leg Distance From Edge To Hole Center Along Width:

0.313 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg has additional hole 0.625 in. Min and 0.626 in. Maximum diameter 0.750 in. From end centered on w of leg; one hole 0.093 in.

Diameter 2.500 in. From 5/8 diameter hole and 0.750 in. From bottom

Material:

Steel or steel comp 1008 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1017 or steel comp 1020

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0