Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-252-9594

Thread Length:

0.620 inches left internal (includes through thread)

Diameter:

0.625 inches

Length:

1.380 inches

Cross-sectional Shape:

Round

Special Features:

Parallel flatted surfaces 0.190 in. Lg spaced 0.492 in. Min 0.502 in. Maximum apart w/inside radius 0.040 in. Max

Material:

Steel comp 1018 or steel comp 1020 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1019 or steel comp 1020

Material Specification:

Astm a108, grade 1018 assn standard 1st material response or astm a108, grade 1020 assn standard 2nd material response or astm a108, grade 1010 assn standard 3rd material response or astm a108, grade 1012 assn standard 4th material response or astm a108, grade 1015 assn standard 5th material response or astm a108, garde 1016 assn standard 6th material response or astm a108, grade 1017 assn standard 7th material response or astm a108, grade 1019 assn standard 8th material response or astm a108, grade 1020 assn standard 7th material response or astm a108, grade 1019 assn standard 8th material response or astm a108, grade 1020 assn standard 9th material response or astm a108, grade 1019 assn standard 8th material response or astm a108, grade 1020 assn standard 9th material response or astm a108, grade 1019 assn standard 8th material response or astm a108, grade 1020 assn standard 9th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Style Designator:

Left internal thread

Shelf Life:

N/a

Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A08900