

View Online at <https://aerobasegroup.com/nsn/5340-01-253-3032>

Mounting Hole Type:

Plain

First Leg Length:

1.380 inches

Second Leg Length:

2.380 inches

Reinforcement Method (non-core):

Rib stiffener both sides

Second Leg Width:

9.250 inches

First Leg Hole Diameter:

0.500 inches

Second Leg Hole Diameter:

0.500 inches

Second Leg Distance Between Hole Centers Along Width:

8.250 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

3.620 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

5.510 inches

First Leg Corner Radius:

0.190 inches

First Leg Distance Between Hole Centers Along Width:

3.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

38.0 degree angle between legs

Material:

Aluminum alloy 5083 or aluminum alloy 5086 or aluminum alloy 5052

Material Specification:

Qq-a-250/6, h321 or h323 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response or qq-a-250/8, h32 federal specification 3rd material response

Surface Treatment:

Paint

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0